

How to order CZ 400DGC

SELECT MODEL

1 Series CZ 400 DGC

Type G Gauge

3 Body material A Aluminum
S SS-316

4 Dial size 3.5 3.5" (80 mm) 4.0 4.0" (100 mm)
4.5 4.5" (115 mm) 6.0 6.0" (150 mm)

5 Connection 4N 1/4" NPT (F) (Std.)
4B 1/4" BSP (F) (with adaptor)
ZZ Special connection sizes using adaptor

6 Porting 1 In-line (Std.) 4 Bottom & Vent
2 Rear / Back 5 Inline & Vent
3 Bottom 6 Inline & Bottom

7 Case SS SS 304 (Std.) SF SS 304 flange

8 Window F Glass (Std.) A Acrylic
T Toughened glass L Safety glass

9 Seals/Diaphragm B Buna-N (Std.) E EPDM
V Viton

10 Range Standard ranges : (Other ranges on request)

mm H2O	50	125	250	600
In H2O	2	5	10	25
mbar	5	-	25	60
kPa	0.5	1.25	2.5	6

11 Options

- 0 None
- C Customer Logo
- D Dual scale
- E Colour band
- F Filter mesh in (+) connection
- N NACE
- S Silicone oil*
- I Oxygen service (Contact factory)
- P DIN plug at back on plastic switch cover
- M1 2" horizontal pipe mounting bracket
- M2 Surface mounting bracket
- M3 2" vertical pipe mounting bracket

* Affects accuracy

Advantages :

Instrument automatically resets after line surges and cold start. This eliminates balancing of differential pressure instrument after such events.

Model

Notes

CZ 300DGC Liquid filling will not have follower pointer.

Ordering code sequence

Before creating ordering code, please refer model wise notes above.

