

## SELECT MODEL

- 1 Series **DX 20**
- 2 Basic options  
 F Float glass (std.)      A Acrylic  
 H Hardened glass
- 3 Liquid filling  
 G Glycerine \*              S Silicone \*
- 4 Dial size  
 3.5 3.5" (80mm)          4.0 4.0" (100 mm)
- 5 Case type  
 SS SS 304 (Std.)          SF SS 304 flange \*\*\*
- 6 Ranges  
 Standard ranges (Other ranges on request)

**DX 10**

<b>bar</b>	<b>0.25</b>	<b>0.4</b>	<b>0.6</b>	<b>1.0</b>	<b>1.6</b>	<b>2.0</b>	<b>2.5</b>	<b>3.0</b>	<b>4.0</b>	<b>6.0</b>	<b>10.0</b>
<b>psi</b>	<b>3.5</b>	<b>6.0</b>	<b>9.0</b>	<b>15</b>	<b>24</b>	<b>30</b>	<b>36</b>	<b>45</b>	<b>60</b>	<b>90</b>	<b>140</b>

**DX 20**

<b>bar</b>	<b>0.16</b>	<b>0.2</b>	<b>0.25</b>	<b>0.4</b>	<b>0.6</b>	<b>1.0</b>	<b>1.6</b>	<b>2.0</b>
<b>psi</b>	<b>2.4</b>	<b>3.0</b>	<b>3.5</b>	<b>6.0</b>	<b>9.0</b>	<b>15</b>	<b>24</b>	<b>30</b>

- 7 Porting  
 1 In-line (Std.)              2 Rear / Back\*\*\*  
 3 Bottom\*\*\*
- 8 Port threading 2x  
 4B 1/4" BSP(F) (Std.)      4N 1/4" NPT (F)  
 ZZ Special connection sizes using adaptor
- 9 Seals  
 B Buna-N                      V Viton
- 10 Pressure  
 100 100bar                      250 250 bar\*\*\*  
 400 400 bar\*\*\*
- 11 Connection  
 0 + left / - right              R + right / - left \*\*\* \*\*
- 12 Mounting  
 0 None                              M1 2" horizontal pipe mounting bracket  
 M2 Surface mounting          M3 2" vertical pipe mounting bracket  
 M4 Engg. polymer mounting bracket
- 13 Switch  
 Select option and specifications

SPST Specifications (AC/DC max)

0	None	+	1 Standard	2	3
S1	One SPST, with a DIN plug		10 VA	40 VA	100 VA
S4	Two SPSTs, with DIN plug		100 V	230 V	300 V
			0.5 Amp	1 Amp	1 Amp
			Adjustable	Adjustable	Adjustable

SPDT Specifications (AC/DC max)

S2	One SPDT, with a DIN plug	+	1 Standard	2	3
S3	Two SPDTs, with DIN plug		3 VA	5 VA	5 VA
			30 V	125 V	175 V
			0.3 Amp	0.25 Amp	0.25 Amp
			Adjustable	Adjustable	Adjustable

- 14 Wiring options  
 W1 DIN plug at top              W2 DIN plug on LP side  
 W3 DIN plug at back              W4 2 DIN plugs for 2 SPDTs (1 on LP side and other on top)
- 15 Other options  
 0 None  
 F Follower pointer on acrylic window\*  
 S Filter mesh in (+) connection  
 C Customer logo  
 E Color band (Available in single scale only)
- 16 Certifications  
 0 None                              C1 Certificate of conformance  
 C2 Accuracy and class          C3 Material test certificate  
 C4 Pressure test

\* Affects accuracy

\*\* Pointer moves from right to left

\*\*\* Only in DX 10