


| | | | | | | | | | | | |
|-----------------|------------------|--|--------------------|------|-----|-----|-----|----|----|----|----|
| 1 Series | GX 100 | | | | | | | | | | |
| 2 Type | G | Gauge | GS Gauge + Switch | | | | | | | | |
| 3 Body material | A | Aluminium | | | | | | | | | |
| 4 Dial Size | 2.5 4.0 | 2.5" (Std.) 4.0" ** | 3.5 3.5" ** | | | | | | | | |
| 5 Window | A | Acrylic | | | | | | | | | |
| 6 Case | SS | SS304 with a rubber ring(standard) | | | | | | | | | |
| 7 Range | bar Psi | <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td>0.75</td> <td>1.0</td> <td>1.6</td> <td>2.0</td> </tr> <tr> <td>10</td> <td>15</td> <td>24</td> <td>30</td> </tr> </table> | | 0.75 | 1.0 | 1.6 | 2.0 | 10 | 15 | 24 | 30 |
| 0.75 | 1.0 | 1.6 | 2.0 | | | | | | | | |
| 10 | 15 | 24 | 30 | | | | | | | | |
| 8 Porting | 1 3 | Inline** Bottom (Std.) (Specify C.D. 54mm or 55mm) | | | | | | | | | |
| 9 Connection | 4N ZZ | 1/4" NPT(F) Std. 4B 1/4" BSP (F) on request Special connection through adaptors | | | | | | | | | |
| 10 Seal | B | Buna-N (Std.) | V Viton on request | | | | | | | | |
| 11 Option | 0 B C E | None Red follower pointer Customer logo Color band (Available in single scale only) | | | | | | | | | |
| 12 Switch | 0 S2 S3 | None 1 SPDT 2 SPDTs Note: Please specify switch set point/s while ordering. It can not be changed later. | | | | | | | | | |

Switch specifications & connection diagram :

| | |
|-------------------|---------------------------------|
| Contact Rating | : 3 VA AC(rms) or DC(max.) |
| Switching current | : 0.30 Amp AC(rms) or DC (max.) |
| Switch Voltage | : 30 V AC (rms) or DC (max.) |
| Lead length | : 1.0 meter |

SPDT Switch



**Longer delivery and switch option not available