


COMBINATIONS

Gauge



Gauge+switch (with a DIN plug on top)



D200 DPG

DP Range : 0 to 0.5 upto 10 bar
0 to 7 upto 150 psi

Specifications

Accuracy	± 5% of the FSD (Ascending)
Migration	Minor from high to low port
Range	0-0.5 to 0-10 bar or equivalent range in other units
First marking on the scale	20% of the FSD
Sensing element	Piston
Wetted parts	Body material, SS 302 spring, ceramic magnet & seals
Case material	Stainless steel (SS 304)
Dial size in inch /mm	2.5"
Mounting	Direct
Maximum working pressure	350 bar
Maximum process temperature	80° C / 175° F
Body material	Aluminum
Seals	Buna-N, Viton & EPDM 'O' rings
Window	Float glass(Std.), toughened glass, acrylic & safety glass.
Connection	1/4" NPT(F) Std. optional 1/4" BSP(F)
Porting	In-line, bottom
Over range protection	Up to the max. working pressure from high & low side
Protection for gauge & switch	IP 65 / NEMA-4

Options

Switches (Adjustable in 20-100% of FSD)

Liquid filling	1 or 2 SPSTs with a DIN plug on top
Red follower pointer	1 SPDT with DIN plug on top
Customer logo	
Dual scale	
Colour band	
Filter mesh in (+) connection	

STANDARD DIMENSIONS :

