

## SELECT MODEL

- 1 Series** D200 DPG
- 2 Type**
  - G Gauge
  - GS Gauge + Switch
- 3 Body material**
  - A Aluminum
  - B Brass
  - S SS-316
- 4 Dial size**
  - 2.5 2.5" (63 mm)
- 5 Connection**
  - 4N 1/4" NPT (F) (Std.)
  - ZZ Special connection sizes using adaptor
  - 4B 1/4" BSP (F)
- 6 Porting**
  - 1 In-line
  - 3 Bottom (Std.)
- 7 Case**
  - S4 SS 304 (Std.)
  - S6 SS 316
- 8 Window**
  - F Glass (Std.)
  - T Toughened glass
  - A Acrylic
  - L Safety glass
- 9 Seals/Diaphragm**
  - B Buna-N (Std.)
  - V Viton
  - E EPDM
- 10 Switch** Select option & Specifications

**Advantages :**  
Instrument automatically resets after line surges and cold start.  
This eliminates balancing of differential pressure instrument after such events.

**Notes**

- For SS 316 case, please contact factory (MOQ applies).
- Liquid filling + Follower pointer available.
- Switch adjustment range between 20-100% of full scale deflection (FSD). For specific details, please contact factory.

0	None
1	One SPST, with a DIN plug †
3	Two SPSTs, with a DIN plug †

+

1 Standard	2	3	4
10 VA	40 VA	100 VA	60 VA
100 V	230 V	300 V	240 V
0.5 Amp	1 Amp	1 Amp	3 Amp
Adjustable	Adjustable	Adjustable	Adjustable

5	One SPDT, with a DIN plug †
---	-----------------------------

+

1 Standard	2	3	4
3 VA	5 VA	5 VA	60 VA
30 V	125 V	175 V	400 V
0.3 Amp	0.25 Amp	0.25 Amp	1 Amp
Adjustable	Adjustable	Adjustable	Factory Set

**Example:** Switch selection 11 is 1 SPST with DIN plug with switch specifications 10VA, 100V, 0.5Amp

† DIN plug mounted on the top.

## 11 Range

**Standard ranges : (Other ranges & units on request)**


Kg/cm <sup>2</sup>	0.5	0.75	1	-	1.6	2	2.5	3	3.5	4	5	-	6	7	9	10
bar	0.5	0.75	1	-	1.6	2	2.5	3	3.5	4	5	-	6	7	9	10
mbar	500	750	1000	-	-	-	-	-	-	-	-	-	-	-	-	-
psi																
kPa	8	-	15	20	25	30	-	40	50	60	-	80	-	100	-	-

## 12 Options

- 0 None
- A Glycerine\*
- B Red follower pointer on acrylic window \*
- C Customer Logo
- D Dual scale
- E Colour band
- F Filter mesh in (+) connection
- S Silicone oil\*
- I Oxygen service (Contact factory)

\* Affects accuracy

## Ordering code sequence



Contact factory for special execution.