

How to order D200DPG

SELECT MODEL

- 1 Series** D200 DPG
- 2 Type** G Gauge
GS Gauge + Switch
- 3 Body material** A Aluminum
- 4 Dial size** 2.5 2.5" (63 mm)
- 5 Connection** 4N 1/4" NPT (F) (Std.) 4B 1/4" BSP(F)
ZZ Special connection sizes using adaptor
- 6 Porting** 1 In-line
3 Bottom (Std.)
- 7 Case** SS SS 304 (Std.)
- 8 Window** F Glass (Std.) A Acrylic
T Toughened glass L Safety glass
- 9 Seals** B Buna-N (Std.) E EPDM
V Viton
- 10 Switch** Select option & Specifications

Advantages :
Instrument automatically resets after line surges and cold start.
This eliminates balancing of differential pressure instrument after such events.

0	None
1	One SPST, with a DIN plug †
3	Two SPSTs, with a DIN plug †

+

SPST Specifications (AC/DC max)		
1 Standard	2	3
10 VA	40 VA	100 VA
100 V	230 V	300 V
0.5 Amp	1 Amp	1 Amp
Adjustable	Adjustable	Adjustable

5	One SPDT, with a DIN plug †
---	-----------------------------

† DIN plug mounted on the top.

+

SPDT Specifications (AC/DC max)		
1 Standard	2	3
3 VA	5 VA	5 VA
30 V	125 V	175 V
0.3 Amp	0.25 Amp	0.25 Amp
Adjustable	Adjustable	Adjustable

11 Range **Standard ranges : (Other ranges on request)**

D200 DPG	Kg/cm ²	0.5	0.75	1	-	1.6	2	2.5	3	3.5	4	5	-	6	7	9	10
	bar	0.5	0.75	1	-	1.6	2	2.5	3	3.5	4	5	-	6	7	9	10
	mbar	500	750	1000	-	-	-	-	-	-	-	-	-	-	-	-	-
	psi	8	-	15	20	25	30	-	40	50	60	-	80	-	100	-	-
	kPa	50	75	100	-	160	200	250	300	350	400	500	-	600	700	900	1000

12 Options

- 0 None
 - A Glycerine*
 - B Red follower pointer on acrylic window *
 - C Customer Logo
 - D Dual scale
 - E Colour band
 - F Filter mesh in (+) connection
 - S Silicone oil*
 - I Oxygen service (Contact factory)
 - K 32mm thick body
- * Affects accuracy

Ordering code sequence

Before creating ordering code, please refer model wise notes above.

